RPII Inspector Issued Report

Issued by: Elliotts Inspections

Date Issued: 23/06/2026

Date Expires: 23/06/2027

RPII Reg Number: AI0223

Place of Inspection: On site at customer

Unique Report Number: 311

Result: Passed Inspection

Unit Details

Description: red and blue front slide combo
Manufacturer: better bounce
Size (m): Width: 3.2 Length: 5.0 Height: 3.1
Serial: 70370
Unit Type: front slide combo
Unit Owner: claires inflatables

User Height/Count

Containing Wall Height: 0.0m
Comment: Lowest wall height taken from adjacent platform.
Tallest Platform Height: 0.6m
Comment:
Tallest User Height: 1.8m
Comment: Calculated using lowest containing wall height minus the platform height or the relevant slide calculations where appropriate.
Internal Play Area Length: 2.35m
Comment:
Internal Play Area Width: 2.1m
Comment:
Negative Adjustment: 0.0m
Comment: Approx square metre are taken by obstacles, biff bash, mounds etc.
Users @ 1.0m: 8 Users @ 1.2m: 7 Users @ 1.5m: 5 Users @ 1.8m: 3

Slide

Slide Platform Height: 0.6m
Comment: slide combo applicable
Containing Wall Height: 0.0m
Comment: slide combo applicable
First Metre Slide Wall Height: 0.0
Comment: slide combo applicable
Remaining Slide Wall Height: 0.0m
Comment: slide combo applicable
Perm Slide Roof Fitted: True
Comment: slide combo applicable
Steps/Clamber Netting Pass/Fail: True
Comment: slide combo applicable
Slide Run Out: 1.0m
Slide Run Out Pass/Fail: True
Comment: slide combo applicable
Slip Sheet Integrity Pass/Fail: True
Comment: slide combo applicable

RPII Inspector Issued Report

Issued by: Elliotts Inspections

Date Issued: 23/06/2026

Date Expires: 23/06/2027

RPII Reg Number: AI0223

Place of Inspection: On site at customer

Unique Report Number: 311

Result: Passed Inspection

Structure

Seam Integrity Pass/Fail: True
Comment: Secure and no loose stitching.
Lock Stitching Pass/Fail: True
Comment: Lock stitching used.
Stitch Length: 4mm
Stitch Length Pass/Fail: True
Comment: Stitching between 3mm - 8mm
Air Loss Pass/Fail: True
Comment: No significant air loss or holes.
Walls and Turrets Vertical Pass/Fail: True
Comment: Walls Vertical and gradient no greater than +-5%
Sharp/Square/Pointed Edges Pass/Fail: True
Comment: No sharp or pointed edges.
Blower Tube Distance: 1.20m
Blower Tube Pass/Fail: True
Comment: Inflate blower tube is at least 1.2m from edge of cone to inflatable.
Unit Stable Pass/Fail: True
Comment: Unit is stable.
Evacuation Time: 30
Evacuation Time Pass/Fail: True
Comment: Evacuation time sufficient for intended users to exit safely under supervision.
Step/Ramp Size: 1.0m
Step/Ramp Size Pass/Fail: True
Comment: Step/Ramp tread depth is equal to or more then 1.5 times the adjacent attached playing area.
Critical Fall Off Height: 0.6m
Critical Fall Off Height Pass/Fail: True
Comment: Critical Fall Off Height is a max of 600mm/0.6m
Critical Fall Off Height: 0.6m
Critical Fall Off Height Pass/Fail: True
Comment: Critical Fall Off Height is a max of 600mm/0.6m
Unit Pressure: 1.19Kpa
Unit Pressure Pass/Fail: True
Comment: Pressure is a minimum of 1.19 KPA
Trough Depth: 70.0mm
Trough Adjacent Panel Width: 450.0mm
Trough Pass/Fail: True
Comment: Trough Depth is no more than one third (1/3) of the adjacent panel width.
Entrapment Pass/Fail: True
Comment: No entrapments.
Markings/ID Pass/Fail: True
Comment: Blower, User Height, Max Users, Unique ID, Year of Manufacture & Address and Standard Version.
Grounding Pass/Fail: True
Comment: 25kg @ 1m, 35kg @ 1.2m

RPII Inspector Issued Report

Issued by: Elliotts Inspections

Date Issued: 23/06/2026

Date Expires: 23/06/2027

RPII Reg Number: AI0223

Place of Inspection: On site at customer

Unique Report Number: 311

Result: Passed Inspection

Anchorage

Total Number of Anchors: 8
Number of Base Anchors: 8
Number of High Anchors: 0
Number of Anchors Pass/Fail: True
Comment: Sufficient number of anchor points per side.
Anchor Accessories Pass/Fail: True
Comment: Produced correct amount of stakes at 380mmx16mm with rounded top and no visible cracks.
Anchors Between 30-45° Pass/Fail: True
Comment: Anchors are at an angle to the ground of 30° to 45°
Anchors Perm Closed Pass/Fail: True
Comment: Metal and permanently closed.
Pull Strength Pass/Fail: True
Comment: Meets the 1600 newton pull requirement test using 163kg pull system

Totally Enclosed

Number of Exits: 0
Number of Exits Pass/Fail: False
Comment: Not Applicable
Number of Exits Pass/Fail: False
Comment: Not Applicable

Materials

Ropes: 18mm
Ropes Pass/Fail: True
Comment: Between 18mm - 45mm. Fixed at both ends, no greater than 20% swing to prevent strangulation.
Clamber Netting Pass/Fail: True
Comment: Not monofilament, no entrapment and at least 12mm diameter, securely knotted and no fraying, securely fastened.
Retention Netting Pass/Fail: True
Comment: Vertical netting > 1m mesh size is no greater than 30mm. Roof neeting mesh size no greater than 8mm.
Zips Pass/Fail: True
Comment: Zips easily open/close and covered. Open both sides where applicable.
Windows Pass/Fail: True
Comment: Retention netting strong enough to support heaviest user for whom it is designed.
Artwork Pass/Fail: True
Comment: Not flaking - Manufacturer to supply conformity report to EN 71-3
Thread Pass/Fail: True
Comment: Manufacturer to provide conformity report to confirm thread is non-rotting yarn and has a tyensile strength of 88 newtows.
Fabric Strength Pass/Fail: True
Comment: Manufacturer to provide conformity report to confirm tensile strength of 1850 and tear stength of 350 newtons.
Fire Retardent Pass/Fail: True
Comment: Manufacturer to provide conformity report to confirm FR.

RPII Inspector Issued Report

Issued by: Elliotts Inspections

Date Issued: 23/06/2026

Date Expires: 23/06/2027

RPII Reg Number: AI0223

Place of Inspection: On site at customer

Unique Report Number: 311

Result: Passed Inspection

Fan/Blower

Blower Size: Reaches 1.0 kpa pressure on a 1.5hp blower.
Return Flap Pass/Fail: True
Finger Probe Test Pass/Fail: True
Comment: 8mm finger probe does not pass and come into contact with any hot or moving part.
PAT Test Pass/Fail: True
Comment: Customer own certificate.
Visual Inspection Pass/Fail: True
Comment: Passes visual inspection and suitable.
Blower Serial: m0160

Risk Assessment

The suitability of all materials used in manufacturing should be taken from conformity reports. Where not available these should be requested from the manufacturer/importer.
Safety aspects should be taken from the user manual provided by the manufacturer. If not provided then this should be requested or created by the controller.
Not to be used in wind speeds in aexcess of 38Kph.
A competant adult should supervise the inflatable and users at all times.
All anchor points to be used at all times.
grounding test suitable for 1.5m users.

Advisory: Operations Manual not presented at time of inspection. Controller advised to obtain or develop the operations manual to ensure that they can demonstrate their duty, safe use and set-up.

Inflatable device inspected for outdoor and indoor use.

Testimony: I certify that the equipment identified above was inspected and complied with the safety criteria required using all relevant sections of the European Standard EN 14960:2019 on the above date.

Inflatable Photo

RPII Inspector Issued Report

Issued by: Elliotts Inspections

Date Issued: 23/06/2026

Date Expires: 23/06/2027

RPII Reg Number: AI0223

Place of Inspection: On site at customer

Unique Report Number: 311

Result: Passed Inspection

Additional Photo 1

Additional Photo 2

Additional Photo 3

Additional Photo 4